

## CONTENTS

<b>PREFACE</b>	viii
<b>ACKNOWLEDGMENTS</b>	xi
<b>OTHER BOOKS BY THE AUTHOR</b>	xii
<b>1 CHARACTERISTICS OF 12-PULSE CONVERTERS</b>	
1.1 BACKGROUND DISCUSSION	1-1
1.2 INTRODUCTION	1-2
1.3 AUTO-CONNECTED METHODS (Paralleled 6-pulse converters)	1-3
1.4 AUTO-CONNECTED 12-PULSE WITH DC FILTER CAPACITOR	1-4
1.5 HYBRID DOUBLE-WOUND TRANSFORMER	1-8
1.6 DOUBLE-WOUND TRANSFORMER METHODS	1-10
1.7 COMPARISON OF SOME PRACTICAL 12-PULSE DIODE CONVERTERS	1-10
1.8 RECOMMENDED 12-PULSE METHODS	1-11
<b>2 SERIES-CONNECTED MULTIPULSE CONVERTER</b>	
2.1 INTRODUCTION	2-1
2.2 ABOUT SERIES CONVERTERS	2-1
2.3 12-PULSE SERIES CONNECTED CIRCUIT MC-106	2-2
2.4 ANALYSIS	2-3
2.5 ADDITIONAL FILTERING	2-5
2.6 CALCULATED RESULTS	2-5
2.7 SUMMARY OF MC-106 12-PULSE CONVERTER FEATURES	2-5
<b>3 TRADE-OFFS FOR HIGH POWER (1200 HP) MULTIPULSE CONVERTERS</b>	
3.1 INTRODUCTION	3-1
3.2 DESIGN PARAMETERS FOR TRADE-OFFS	3-1
3.3 TRADE-OFF METHODOLOGY	3-2
3.4 COSTING METHODOLOGY	3-2
3.4.1 Magnetic Component Cost	3-2
3.4.1.1 Calculation of Component kVA and Cost	3-2
3.4.2 Cost of Losses	3-3
3.5 12-PULSE WITH HALF-POWER STANDARD DELTA/WYE TRANSFORMER	3-3
3.5.1 Computer Simulation and Results	3-5
3.5.2 Application Issues	3-7
3.5.3 Summary of Magnetic Component Costs	3-7
3.6 TWELVE-PULSE WITH DIFFERENTIAL-DELTA AUTOTRANSFORMER	3-8
3.6.1 Equivalent Double-Wound kVA of Phase-Shifting Transformer	3-9
3.6.2 Computer Simulation and Results	3-10
3.6.3 Application Issues	3-12
3.6.4 Summary of Magnetic Component Costs	3-12
3.7 EIGHTEEN-PULSE WITH FORK PHASE-SHIFTING AUTOTRANSFORMER	3-13
3.7.1 Equivalent Double-Wound kVA of Phase-Shifting Transformer	3-14
3.7.2 Computer Simulation and Results	3-16
3.7.3 Application Issues	3-17
3.7.4 Summary of Magnetic Component Costs	3-18
3.8 NEW 18-PULSE "WINDMILL" AUTOTRANSFORMER	3-18

3.8.1	Equivalent Double-Wound kVA of Phase-Shifting Transformer	3-19
3.8.2	Computer Simulation and Results	3-20
3.8.3	Application Issues	3-21
3.8.4	Summary of Magnetic Component Costs	3-22
3.9	SUMMARY OF TRADE-OFF STUDY FOR 480-V 1200-HP CONVERTERS	3-22
3.10	SIZE AND WEIGHT CONSIDERATIONS FOR TRANSFORMERS	3-24
3.10.1	Idealized kVA and Size Factors	3-24
3.10.2	Practical Results	3-25
<b>4</b>	<b>DESIGN FEATURES OF 18-PULSE CONVERTERS</b>	
4.1	INTRODUCTION AND HIGHLIGHTS	4-1
4.2	TESTING THE FORK PHASE-SHIFTING TRANSFORMER	4-5
4.2.1	Introduction	4-5
4.2.2	Open-circuit Tests	4-5
4.2.3	Commutating Reactance	4-5
4.2.4	Production Tests to Verify Phase Shift	4-6
4.2.5	Production Tests for Lumped Commutating Reactance	4-7
4.2.6	Prototype Transformer Tests	4-8
4.2.7	Prototype Tests to Establish Coil-to-Coil Coupling Factors	4-8
4.2.8	Conductor Eddy Currents, Stray Losses, and Skin Effects	4-9
4.2.8.1	Skin Effects	4-10
4.2.8.2	Eddy Currents	4-10
4.3	COMPUTER SIMULATION AND LEAKAGE CALCULATIONS	4-11
4.3.1	Summary	4-11
4.3.2	Lumped Impedance Simulation Method Using ECA	4-12
4.3.3	Coupled-Coil Simulation Method	4-12
4.3.4	Commutation Paths	4-12
4.3.5	Transformer Simulation with Lumped Parameters	4-13
4.3.6	Measured Results and Lumped Parameters for a 200-HP Design	4-13
4.3.7	Transformer Simulation with Coupled Coils	4-14
4.4	CALCULATION OF COIL LEAKAGES	4-15
4.4.1	Introduction	4-15
4.4.2	Method for Calculating Commutation Reactance	4-16
4.4.3	Applying the Formulas	4-16
4.4.4	Practical Example of Coil-to-Coil Leakage Reactance	4-18
4.4.5	Calculation of "Short" Commutation Reactance	4-19
4.4.6	Measurement of Coupling Factors	4-19
4.5	SIMULATIONS USING LUMPED AND COUPLED COIL PARAMETERS	4-21
4.5.1	Simulation Using Lumped Parameters	4-21
4.5.2	Calculated and Measured Converter Performance	4-22
4.5.3	Simulation Using Coupled Coils	4-23
4.6	REVIEW OF SIMULATION TECHNIQUES	4-25
4.7	CONCLUSIONS	4-26
<b>5</b>	<b>MULTIPULSE CONCEPTS FOR SINGLE-PHASE LOADS</b>	
5.1	INTRODUCTION	5-1
5.2	TYPICAL SINGLE-PHASE SYSTEM INSTALLATIONS	5-1
5.3	MULTIPLE TRANSFORMERS FOR HARMONIC CANCELLATION	5-2
5.3.1	Harmonic Performance Using Two Transformers	5-3
5.4	SINGLE TRANSFORMER TO ACHIEVE HARMONIC CANCELLATION	5-5

## **6 MULTIPULSE TRANSFORMER INRUSH CURRENT**

6.1 INTRODUCTION	6-1
6.2 ESTIMATION OF MAXIMUM INRUSH CURRENT	6-2
6.2.1 Magnetic Materials	6-2
6.2.2 Estimation of Residual Flux	6-5
6.2.3 Estimation of Inductance with Current	6-5
6.2.4 Calculation of Three-Phase AC Line Reactor Inductance Versus Current	6-6
6.2.5 Transformer Magnetizing Characteristics	6-8
6.2.6 Magnetizing Inductance as a Function of Current	6-8
6.3 SIMULATION OF TRANSFORMER AND CONVERTER	6-10
6.4 CALCULATION OF TRANSFORMER WINDING INDUCTANCE	6-11
6.4.1 Estimated Magnetizing Current using Calculated Inductance	6-13
6.5 MEASURED TRANSFORMER MAGNETIZING CURRENT	6-14
6.6 THREE-PHASE SIMULATION AND INRUSH CALCULATIONS	6-14
6.7 MEASUREMENT OF COIL SATURATION PARAMETERS	6-17
6.7.1 Estimation of Coil Inductance	6-18
6.7.2 Estimation of Maximum Residual Flux	6-19
6.8 SUMMARY	6-20

## **7 THE EFFECTS OF DC BIAS ON TRANSFORMER MAGNETIZING CURRENT**

7.1 INTRODUCTION	7-1
7.2 GENERAL ANALYSIS	7-1
7.3 EXAMPLE OF DC BIAS ON A NONLINEAR CORE	7-2
7.4 COMPUTER SIMULATIONS OF DC BIAS EFFECTS	7-2
7.5 SUMMARY	7-5

## **8 IRON-CORE, AIR-GAPPED INDUCTORS**

8.1 INTRODUCTION	8-1
8.2 INDUCTOR WITH 2 WINDINGS	8-1
8.3 THREE-LIMB REACTOR	8-2
8.4 ANALYSIS OF 3-LIMB, 3-COIL REACTOR	8-4
8.5 VARIATIONS ON A 3-LIMB, 3-COIL REACTOR	8-5
8.6 MULTI-LIMB CORES FOR INTERPHASE REACTORS/TRANSFORMERS	8-7

## **9 PHASE-STAGGERED LOADS FOR HARMONIC AND NOTCH REDUCTION**

9.1 INTRODUCTION	9-1
9.2 SINGLE SYSTEM TRANSFORMER FOR MULTIPLE 6-PULSE LOADS	9-3
9.2.1 Transformer Impedance and Load Effects	9-3
9.3 SINGLE TRANSFORMER FOR MULTIPLE 12-PULSE LOADS	9-4
9.4 PHASE STAGGERING WITH UNCONVENTIONAL PHASE SHIFTS	9-7
9.4.1 Analysis	9-7
9.4.2 Example of Multipulse by Staggering with Unconventional Phase Angles	9-9

## **10 BACKGROUND DISTORTION AND HARMONIC MEASUREMENT**

10.1 INTRODUCTION	10-1
10.2 GENERAL OBSERVATIONS	10-1
10.2.1 The Position of Measurements	10-1
10.2.2 Measurement of Voltage Distortion	10-1
10.2.3 Measurement of Harmonic Currents	10-1

10.3 HARMONIC EFFECTS OF DIFFERENT LOADS	10-2
10.4 STANDARDIZING CURRENT HARMONIC MEASUREMENTS	10-3
10.5 EQUIVALENT HARMONIC CURRENT	10-4
10.6 VOLTAGE UNBALANCE	10-5
10.6.1 Distortion Measurements in the Presence of Voltage Unbalance	10-5
10.6.2 Determining the Amount of Voltage Unbalance	10-6
10.7 DESIGN GUIDES FOR COMPUTER SIMULATION AND DESIGN	10-6
10.8 SUMMARY	10-7
10-9 VOLTAGE UNBALANCE AND SEQUENCE CALCULATIONS	10-7
<b>APPENDIXES</b>	
A-1 SHORT CIRCUITS IN MULTIPULSE AUTOTRANSFORMERS	A1-1
A-2 PHASE-SHIFTING TRANSFORMERS	A2-1
NOTES ON TRANSFORMER CONNECTIONS	A2-3
A-3 MODELING TRANSFORMERS WITH COUPLED COILS	A3-1
2-COIL, 3-COIL, 4-COIL INDUCTORS	A3-1
5-COIL, 6-COIL, 7-COIL INDUCTORS	A3-6
MODELING A COMPLETE CIRCUIT	A3-11
MODELING IDEAL AND NEAR-IDEAL COUPLED COILS/TRANSFORMERS	A3-17
A-4 THREE-LIMB, THREE-PHASE TRANSFORMERS	A4-1
CALCULATION OF ZERO-SEQUENCE IMPEDANCE	A4-3
A-5 THIRD HARMONICS IN THREE-PHASE SYSTEMS	A5-1
RATIONALE FOR 3rd HARMONIC LIMITS TO BE INCLUDED IN IEEE519	A5-6
A-6 VOLTAGE UNBALANCE AND SEQUENCE CALCULATIONS	A6-1
A-7 APPLYING LEAKAGE REACTANCE CALCULATION FORMULAS	A7-1
A-8 GTO/SCR SIMULATION	A8-1
A-9 TOTAL HARMONIC DISTORTION FACTORS	A9-1
A-10 HIGHER PULSE NUMBER CONVERTERS	A10-1
A-11 CURRENTS IN A DELTA WITH UNBALANCED IMPEDANCES	A11-1
<b>BIBLIOGRAPHY</b>	B-1
<b>INDEX</b>	I-1